

Type	Spec.	Part No.	Aspect Ratio	External Dimension	View Area Dimension	Active Area Dimension	Thickness
4-wire	2.2"	TTW4022023	4:3	37.60 * 51.10 mm	34.20 * 45.60 mm	32.68 * 44.50 mm	1.0 mm
4-wire	2.5"	TTW4025013	4:3	43.50 * 60.20 mm	39.00 * 51.00 mm	39.00 * 51.00 mm	1.0 mm
4-wire	2.8"	TTW4028005	4:3	53.50 * 56.10 mm	49.30 * 50.40 mm	49.30 * 50.40 mm	1.0 mm
4-wire	3.5"	TTW4035032	4:3	63.90 * 76.90 mm	53.56 * 71.08 mm	52.36 * 69.88 mm	1.0 mm
4-wire	4.0"	TTW4040003	4:3	64.90 * 97.90 mm	53.00 * 88.00 mm	51.00 * 86.00 mm	1.4 mm
4-wire	4.2"	TTW4042008	4:3	68.30 * 101.83 mm	58.40 * 94.50 mm	55.58 * 91.68 mm	1.0 mm
4-wire	4.3"	TTW4043003	4:3	50.00 * 113.00 mm	40.00 * 105.00 mm	38.00 * 103.00 mm	1.4 mm
4-wire	4.5"	TTW4045011	4:3	64.00 * 105.36 mm	57.60 * 97.96 mm	57.60 * 97.96 mm	1.4 mm
4-wire	5.7"	TTW4057004	4:3	104.70 * 132.50 mm	94.70 * 123.00 mm	87.70 * 116.00 mm	1.4 mm
4-wire	6.2"	TTW4062026	16:10	90.00 * 150.00 mm	80.00 * 140.30 mm	77.20 * 137.50 mm	1.4 mm
4-wire	6.5"	TTW4065003	16:10	89.30 * 155.00 mm	80.00 * 142.80 mm	80.00 * 142.80 mm	1.4 mm
4-wire	6.5"	TTW4065013	16:10	116.50 * 149.00 mm	102.00 * 135.00 mm	99.00 * 132.00 mm	1.0 mm
4-wire	7.0"	TTW4070062	16:10	105.40 * 168.40 mm	93.40 * 157.00 mm	91.90 * 154.90 mm	1.4 mm
4-wire	7.0"	TTW4070076	16:10	106.00 * 165.00 mm	93.50 * 155.00 mm	91.00 * 152.00 mm	1.4 mm
4-wire	7.0"	TTW4070020	16:10	100.10 * 165.00 mm	88.50 * 155.60 mm	86.50 * 153.60 mm	1.4 mm
4-wire	7.0"	TTW4070081	16:10	100.00 * 165.00 mm	89.50 * 157.00 mm	85.50 * 153.00 mm	1.4 mm
4-wire	7.0"	TTW4070026	16:10	99.60 * 164.50 mm	88.50 * 155.50 mm	84.00 * 151.50 mm	1.4 mm
4-wire	7.0"	TTW4070050	16:10	100.00 * 165.00 mm	88.57 * 156.00 mm	86.57 * 154.00 mm	1.4 mm
4-wire	7.1"	TTW4071017	16:10	100.00 * 164.90 mm	87.20 * 154.90 mm	87.20 * 154.90 mm	1.4 mm

Type	Spec.	Part No.	Aspect Ratio	External Dimension	View Area Dimension	Active Area Dimension	Thickness
5-wire	12.1"	TTW5121005	4:3	206.00 * 271.00 mm	190.00 * 252.00 mm	186.00 * 248.00 mm	2.0 mm
5-wire	15.1"	TTW5151009	4:3	247.00 * 322.00 mm	235.00 * 308.50 mm	228.00 * 303.00 mm	2.0 mm
5-wire	17.1"	TTW5171003	4:3	294.50 * 366.00 mm	274.00 * 342.00 mm	266.50 * 334.00 mm	2.0 mm
5-wire	17.1"	TTW5170010	4:3(slim margin)	288.00 * 356.00 mm	269.00 * 337.00 mm	264.50 * 333.00 mm	2.0 mm
5-wire	18.5"	TTW5185002	16:10	253.60 * 429.37 mm	234.00 * 413.40 mm	230.40 * 409.80 mm	2.0 mm
5-wire	19"	TTW5190002	4:3	330.00 * 404.50 mm	305.50 * 381.00 mm	300.50 * 376.00 mm	2.0 mm
5-wire	19.1"	TTW5190009	16:10	278.00 * 428.00 mm	257.00 * 410.50 mm	253.00 * 406.50 mm	2.0 mm
5-wire	22"	TTW5220003	16:10	315.00 * 494.00 mm	294.00 * 468.00 mm	294.00 * 468.00 mm	2.0 mm

Type	Spec.	Part No.	Aspect Ratio	External Dimension	View Area Dimension	Active Area Dimension	Thickness
4-wire	8.0"	TTW4080015	4:3	141.00 * 183.00 mm	124.80 * 164.80 mm	121.80 * 161.80 mm	1.4 mm
4-wire	8.3"	TTW4083001	4:3	149.00 * 184.80 mm	130.50 * 172.80 mm	126.50 * 168.80 mm	1.4 mm
4-wire	8.9"	TTW4090002	16:10	124.80 * 204.90 mm	116.40 * 198.30 mm	114.40 * 196.30 mm	1.4 mm
4-wire	10.2"	TTW4102001	16:10	145.90 * 235.00 mm	136.11 * 224.90 mm	133.20 * 222.00 mm	2.0 mm
4-wire	10.4"	TTW4104007	4:3	172.95 * 225.55 mm	162.20 * 215.00 mm	158.80 * 211.20 mm	2.0 mm
4-wire	12.1"	TTW4121001	4:3	204.00 * 268.00 mm	188.00 * 250.00 mm	185.00 * 246.00 mm	2.0 mm
4-wire	13.3"	TTW4133002	4:3	299.00 * 195.00 mm	289.50 * 182.20 mm	286.08 * 178.80 mm	2.0 mm
4-wire	14.3"	TTW4143001	4:3	227.00 * 298.00 mm	218.00 * 289.00 mm	214.00 * 285.00 mm	2.0 mm
4-wire	15.1"	TTW4151003	4:3	247.00 * 322.00 mm	235.00 * 310.00 mm	228.00 * 304.00 mm	2.0 mm
4-wire	15.4"	TTW4154001	16:10	331.20 * 342.00 mm	207.00 * 223.00 mm	207.00 * 223.00 mm	2.0 mm
4-wire	15.6"	TTW4155001	16:10	215.90 * 363.80 mm	196.80 * 347.50 mm	193.50 * 344.20 mm	2.0 mm
4-wire	17"	TTW4171002	4:3	288.00 * 355.00 mm	275.00 * 341.50 mm	269.00 * 337.00 mm	2.0 mm
4-wire	19.1"	TTW4190001	4:3	323.00 * 396.00 mm	304.00 * 377.00 mm	300.00 * 375.00 mm	2.0 mm
4-wire	15.1"	TTW4150001	16:10	217.00 * 346.20 mm	207.00 * 331.20 mm	203.00 * 327.20 mm	2.0 mm
4-wire	17.1"	TTW4170003	16:10	239.50 * 382.20 mm	229.50 * 367.20 mm	225.50 * 363.20 mm	2.0 mm
4-wire	19.1"	TTW4190003	16:10	266.50 * 426.40 mm	256.50 * 410.40 mm	252.50 * 406.40 mm	2.0 mm
4-wire	22"	TTW4022002	16:10	318.00 * 491.00 mm	300.00 * 477.00 mm	297.60 * 475.00 mm	2.0 mm
5-wire	10.2"	TTW5102004	16:10	147.50 * 235.70 mm	135.90 * 224.80 mm	132.90 * 221.80 mm	1.4 mm
5-wire	10.4"	TTW5104005	4:3	163.80 * 215.90 mm	167.80 * 219.90 mm	186.60 * 249.00 mm	2.0 mm